



iX4 series



Best Value in light industrial printer class



Best Label-saving Protocol!



Before



Manually check items and hand writing records often cause error then waste time and money.

After




electronic record of items, quantities, and time to prevent error, save time and money.


Application



Warehouse



Manufacturing



Transportation & Logistics



Rich functions to make daily work simple and easy



New Panel Design

Enlarged push button switches make it convenient for users wearing gloves.



Ultra Friendly Calibration Modes

Single key Intelli- and Smart-mode calibration performing tasks immediately after installation.



Seamless-converting to Argox printers!

Automatic Language Emulation Detection

Automatic adopting commonly used printer control languages for maximized user friendliness. (Auto-Detection & Auto-Conversion)



Multiple Interfaces

Built-in Ethernet, Dual USB hosts, USB device, RS-232, and it can be expanded with Wi-Fi, GPIO card/Parallel port.

*Sales representative for demonstration video.

(iX4-240 only)

Print Specifications	iX4-200	iX4-240
Printing Method	Direct Thermal & Thermal Transfer	
Printing Resolution	203 dpi (8 dots/mm)	
Printing Speed	Max. 6 ips	
Printing Length	Max. 100"(2540 mm)	
Printing Width	Max. 4.13"(105 mm)	
Memory	32 MB SDRAM, 16MB Flash ROM (USB storage up to 32GB)	
CPU Type	32 bit RISC microprocessor	
Consumables Specifications		
Sensors	Reflective sensor x 1 (Movable) & Transmissive sensor x 1(Movable)	
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper	
Media	Max. width:4.48"(114mm). Min. width: 1" (25.4 mm). Thickness: 0.0025"~0.01" (0.0635mm~0.254mm) 8.26"(210mm)OD on a 3"(76mm) ID core. 7"(177.8mm) OD on a 1.5"(38mm) ID core	
Ribbon	Max. width:4.4"(112mm). Min. width: 1" (25.4 mm). Length:max 450m Wax, Max OD 3.2" (81.3mm). Core size ID 1"(25.4mm). Wax, Wax/Resin, Resin (Ribbon wound ink-side out or ink-side in: auto-detect)	
Fonts & Symbolologies		
Fonts	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation Soft fonts are downloadable Ability to print any Windows True Type font easily. Support scalable font	
1D Barcodes	UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR (NW-7), ITF, Industrial 2of5, MSI, UPCadd-on code, POSTNET, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1DataBar Limited, GS1 DataBar Expanded, GS1DataBar Expanded Stacked	
2D Barcodes	QR Code, PDF417 (includingMicroPDF), DataMatrix (ECC200), GS1 DataMatrix, MaxiCode	
Graphics	PPLA: PCX, BMP, IMG, HEX,GDI PPLB: PCX, BMP, Binary raster, GDI PPLZ: GRF, Hex, GDI	
Emulation	PPLA, PPLB, PPLZ	
Interface Characteristics and Integration		
Operation Interface	LED indicator x 3, Button x 3, LCD Display x 1	
Communication Interface	USB device, RS-232	USB device, RS-232, Ethernet, USB host x 2
Real Time Clock (RTC)	N/A	
Drivers	Windows Driver for Vista/ Win7/ Win8/ Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver	
Software	BarTender, Printer Tool	
Database Link	Argobar Pro support ODBC Database Connection: Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE(*.dbf)	
Operating & Environment Characteristics		
Power Source	Internal Universal Switching Power supply. Input voltage: 100~240V, 50~60Hz	
Operation Environment	Operation Temperature: 40°F~104°F (4°C~40°C), 0% ~ 90% non-condensing, Storage Temperature: -4°F~122°F (-20°C~50°C)	
Agency Listing	CE, CB, cULus, FCC, ICES, Energy Star, RoHS, BSMI	
Physical Characteristics		
Printer Dimensions	W 257 mm x H 263 mm x D 432 mm	
Printer Weight	29lbs (13 kg)	

*Argox reserves the right to enhance and modify the specification without prior notice.
Please check Argox sales representative for most updated specifications.

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



QLM Label Makers Sdn Bhd

214920V

No. 7, Jalan TPP 6/6, Taman Perindustrian Puchong 6, 47100 Puchong, Selangor.

p +603 8062 7823

f +603 8063 7823

SST No: B16-1808-22000165

e malaysia@qlmgroup.com